



MK-Note Block Diagram -- AMD CONGO



PCB STACK UP

LAYER 1 : TOP
LAYER 2 : SGND
LAYER 3 : IN1
LAYER 4 : SVCC
LAYER 5 : IN2
LAYER 6 : IN3
LAYER 7 : SGND1
LAYER 8 : BOT








AM2-BGA-27-27-812-01










CPU

Processor Memory Interface




CPU






PROCESSOR POWER AND GROUND

DECOUPLING BETWEEN PROCESSOR AND DIMMs PLACE CLOSE TO PROCESSOR AS POSSIBLE




BOTTOM SIDE DECOUPLING



Quanta Computer Inc.



PROJECT : Congo

Close to NB within 1"



RS740/RX780/RS780 POWER DIFFERENCE TABLE

PIN NAME	RS740	RX780	RS780	PIN NAME	RS740	RX780	RS780
VDDHT	NC	+1.1V	+1.1V	IOPLLVD	+1.2V	NC	+1.1V
VDDHTRX	NC	+1.1V	+1.1V	AVDD	+3.3V	NC	+3.3V
VDDHTTX	+1.2V	+1.2V	+1.2V	AVDDDI	+1.8V	NC	+1.8V
VDDA18PCIE	NC	+1.8V	+1.8V	AVDDQ	+1.8V	NC	+1.8V
VDDG18	+1.8V	+1.8V	+1.8V	PLLVD	+1.2V	NC	+1.1V
VDD18_MEM	NC	NC	+1.8V	PLLVD18	+1.8V	NC	+1.8V
VDDPCIE	+1.2V	+1.1V	+1.1V	VDDA18PCIEPLL	+1.2V	+1.8V	+1.8V
VDDC	+1.2V	+1.1V	+1.1V	VDDA18HTPLL	+1.8V	+1.8V	+1.8V
VDD_MEM	+1.8V/1.5V	NC	+1.8V/1.5V	VDDLTP18	+1.8V	NC	+1.8V
VDDG33	+3.3V	NC	+3.3V	VDDL18	+1.8V	NC	+1.8V
IOPLLVD18	+1.8V	NC	+1.8V	VDDL133	+3.3V	NC	NC




RS780





Quanta Computer Inc.


PROJECT : Congo

RTC XTAL




RTC







PLACE SATA AC COUPLING CAPS CLOSE TO SB700

SATA HDD



NOTE:

Resistor IS 1K 1% FOR 25MHZ
XTAL, 4.99K 1% FOR 100MHZ
INTERNAL CLOCK



U32B








SB710
Part 2 of 5

SERIAL ATA

SPI ROM

HW MONITOR

ATA 66/100/133




Quanta Computer Inc.

PROJECT : Congo

Size	Document Number	Rev
	SB710-SATA/IDE/HWM/SPI 3/4	1A
Date:	Thursday, October 22, 2009	Sheet 12 of 42


SB710
Part 3 of 5





REQUIRED STRAPS

	PCI_CLK2	PCI_CLK3	PCI_CLK4	PCI_CLK5	LPC_CLK0
PULL HIGH	BOOTFAIL TIMER ENABLED <small>DEFAULT</small>	USE DEBUG STRAPS	RESERVED	RESERVED	EC ENABLED
PULL LOW	BOOTFAIL TIMER DISABLED	IGNORE DEBUG STRAPS <small>DEFAULT</small>			EC DISABLED <small>DEFAULT</small>




NOTE: SB710 HAS INTERNAL 15K PULL UP RESISTOR FOR RTC_CLK

NOTE: SB710 HAS INTERNAL 15K PULL UP RESISTOR FOR SB_GPIO16,SB_GPIO17.

	LPC_CLK1	RTC_CLK	ACZ_RST#	GP17	GP16
PULL HIGH	CLKGEN ENABLED	INTERNAL RTC <small>DEFAULT</small>	ENABLE PCI MEM BOOT	ROM TYPE: H, H = Reserved H, L = SPI ROM	
PULL LOW	CLKGEN DISABLED <small>DEFAULT</small>	EXT. RTC (PD on X1, apply 32KHz to RTC_CLK)	DISABLE PCI MEM BOOT <small>DEFAULT</small>	L, H = LPC ROM L, L = FWB ROM	<small>DEFAULT</small>

DEBUG STRAPS


SB710 HAS 15K INTERNAL PU FOR PCI_AD[28:23]



REQUIRED STRAPS

	PCI_AD28	PCI_AD27	PCI_AD26	PCI_AD25	PCI_AD24	PCI_AD23	PCI_AD29	PCI_AD30
PULL HIGH	USE LONG RESET <small>DEFAULT</small>	USE PCI PLL <small>DEFAULT</small>	USE ACPI BCLK <small>DEFAULT</small>	USE IDE PLL <small>DEFAULT</small>	USE DEFAULT PCIE STRAPS <small>DEFAULT</small>	RESERVED		
PULL LOW	USE SHORT RESET	BYPASS PCI PLL	BYPASS ACPI BCLK	BYPASS IDE PLL	USE EEPROM PCIE STRAPS		RESERVED	RESERVED

NB/SB POWER GOOD CIRCUIT




Quanta Computer Inc.



PROJECT : Congo

Size	Document Number	Rev
	SB710-STRAPS & PWRGD	1A
Date:	Thursday, October 22, 2009	Sheet 14 of 42



LCDVCC






LVDS (11.6")
(1024x600,
1366x768)



Back light





CAMERA VCC Control









Quanta Computer Inc.

PROJECT : Congo


Size	Document Number	Rev
	LCD + CAMERA CONN	1A
Date:	Thursday, October 22, 2009	Sheet 16 of 42




AVDD_3.3 pin is output of internal LDO. Do NOT connect to external supply.





LANVCC




For RTL8102EL/8103EL, use this block.




For RTL8111DL, use this block




Transformer




RJ45 Connector



C70 is only for RTL8111DL.

Pin48
Trace width>60mil,
Trace length<200mil

Note 1: The Trace length between L1 and 8111DL's Pin 1 must be within 0.5 cm. C5 and C8 to L1 must be within 0.5cm. Refer to Layout guide for more detail.




Quanta Computer Inc.

PROJECT : Congo

Size Document Number
PROJECT : LAN(RTL8103EL/8111DL)
Date: Thursday, October 22, 2009 Sheet 19 of 42

DC Current rating: 0.5 A





Quanta Computer Inc.

PROJECT : Congo

Size	Document Number	Rev
	SATA	1A
Date:	Thursday, October 22, 2009	Sheet 20 of 42

21

If mount R97, R95, R94.
R102 should mount 49K





Quanta Computer Inc.
PROJECT : Congo






PROJECT : Congo

USB x 3

Size	Document Number	Rev
	USB x 3	1A
Date:	Thursday, October 22, 2009	Sheet 21 of 42

Rev
1A






Quanta Computer Inc.


PROJECT : Congo

SIM Card CONN




Layout Note:
UIM_RESET, UIM_CLK, UIM_DATA routing as short as possible

MiniCard WWAN connector




Quanta Computer Inc.
PROJECT : Congo


Size	Document Number	Rev
	WWAN	1A
Date:	Thursday, October 22, 2009	Sheet 24 of 42






G-SENSOR (2-Axial)



Discrete TPM





KEYBOARD








26

Touch pad




TRACK POINT





CPU FAN

FANPWR = 1.6*VSET




Quanta Computer Inc.



PROJECT : Congo

FAN/Thermal


Rev
1A

Size	Document Number	Rev
	FAN/Thermal	1A
Date:	Thursday, October 22, 2009	Sheet 28 of 42

















Quanta Computer Inc.

PROJECT : Congo


Size	Document Number	Rev
	VCC1.5 / VCC2.5 (RT9025)	1A
Date:	Thursday, October 22, 2009	Sheet 34 of 42




Quanta Computer Inc.

PROJECT : Congo


Size	Document Number	Rev
	+NB_CORE (MAX8792)	1A
Date:	Thursday, October 22, 2009	Sheet 35 of 42






DISCHARGE


+3V, +5V, +2.5V, +1.5V



+1.1V, +1.2V, +NB_CORE




3V_S5, 5V_S5, 1.2V_S5






LANVCC

CPU_CORE



3VSUS, 5VSUS, 1.8VSUS, +SMDDR_VTERM



Quanta Computer Inc.
PROJECT : Congo

PAGE#	DESCRIPTION	NOTE	PAGE#	DESCRIPTION	NOTE
1	BLOCK DIAGRAM		36	1.2V/1.1V (RT8204)	
2	CLK_GEN_SLG8SP628		37	VCore(MAX8799)	
3	K8G BGA HT I/F 1/4		38	Discharge	
4	K8G BGA DDR2 MEMORY I/F 2/4		39	SYSTEM INFORMATION	
5	K8G BGA CTRL & DEBUG 3/4		40	Power On Sequence	
6	K8G BGA PWR & GND 4/4		41	FL3B Pos Sequence Timing	
7	RS780-HT/PCIE/SPMEM I/F 1/3		42	EC Tracking Record A	
8	RS780-SYSTEM/STRAPS I/F 2/3				
9	RS780-POWER/GND 3/3				
10	SB710-PCIE/PCI/CPU/LPC 1/4				
11	SB710-ACPI/GPIO/USB/AZ 2/4				
12	SB710-SATA/IDE/HWM/SPI3/4				
13	SB710-PWR/DECOUPLING 4/4				
14	SB710-STRAPS & PWRGD				
15	DDR2 SODIMMS & TERMINATOR				
16	LCD/CAMERA				
17	CRT CONN				
18	AUDIO (ALC269VB, SPK)				
19	LAN(RTL8103EL/8111DL)				
20	SATA				
21	USB x 3				
22	Card Reader-RTL5159				
23	WLAN				
24	WWAN				
25	BT/G-SENSOR/TPM				
26	KB/TP				
27	SW/LED/RFID_EEPROM				
28	FAN/Thermal				
29	KBC IT8502E				
30	Screw Hole/EMI				
31	Charger (ISL88731A)				
32	3V/5V (ISL6237)				
33	DDR 1.8V(TPS51116)				
34	VCC1.5 / VCC2.5 (RT9025)				
35	NB_CORE (MAX8792)				

RS780 SM BUS

RS780 I2C (S0)	I2C and AUX Function Define
DAC_SCL DAC_SDA	CRT (+5V)
I2C_CLK I2C_DATA	LVDS (+3V)
DDC_CLK0/AUX0N DDC_DATA1/AUX0P	HDMI (+5V)
DDC_CLK1/AUX1N DDC_DATA1/AUX1P	not used

SB710 SM BUS

SB710 SMBUS	SMBUS Function Define
SMBCLK0 SMBDAT0 (+3V)	DDR / DDR THER / CLOCK GEN
SMBCLK1 SMBDAT1 (+3V_S5)	LAN IC//WI-FI
SMBCLK2 SMBDAT2 (+3V_S5)	not used


KBC(EC) SM BUS


KBC SMBUS (+3VPCU)	SMBUS Function Define
MBCLK MBDAT	BATTERY (+3VPCU)
2ND_MBCLK 2ND_MBDATA	CPU THER SENSOR(+3V) EC EEPROM (+3VPCU)
3ND_MBCLK 3ND_MBDATA	G-SENSOR(+3VS5)



Quanta Computer Inc.

PROJECT : Congo





T1	>16ms
T2	20ms
T3	5ms
T4	1ms
T5	15ms
T6	5ms
T7	5ms
T8	15ms
T9	108ms

FL3B MK-Note Congo Schematic EC Tracking Record A (for SDV --> SIV)08 /27/ 2009

EC #	Page	CMVC #	Description	Date	Part Affected
A00	31		Change PJ2 pin assignment		
A01	29,11		Change BT_ON# to Test point on EC and BT_ON controlled by SB710 pinW17 (GPIO0)		
A02	26		Change CN8 pin number (13pin-->10pin)		
A03	24		C236 change footprint size		
A04	35		Modify PQ56,PQ57, PL13 footprint		
A05	36		Modify PQ60 footprint		
A06	37		Modify PR165,PR168,PC107,PR17,PR178,PR180 footprint		
A07	27		Delete SW1		
A08	37		Delete PQ53		
A09	32		Delete PJP18,PJP15		
A10	33		Delete PJP16,PJP17		
A11	34		Delete PJP8,PJP6,PJP7		
A12	35		Delete PJP3		
A13	36		Delete PJP5,PJP12		
A14	37		Delete PJP10		
A15	28		Delete Q27 & Mount R344		
A16	05		R73 unmount & Add R416		
A17	05		Exchange Q8 pin1 and pin3 net connection , Unmount R24		
A18	11		Unmount R142,R131,R145,R111 & Mount R143,R132,R139,R110		
A19	22		Change CN10 symbol and footprint		
A20	18		Add CN24 &DIGITAL_MIC Circuit		
A21	21		Unmount R92,R91,R96 & Mount R90,R93		
A22	29		Add MB_ID circuit ,Resume_RST move to default high.(Pin.33-->99) ,Delete D5		
A23	23		C295 change footprint size		
A24	29,21		Add USBCHR_ON# on EC pin97 & U31 pin4		
A25	11		Change USB5--NC,Exchange USB2 & USB4 ,USB5--USB8		
A26	33		Power combustion test need change PQ8 package		
A27	38		Change PR84 from 1M to 100K for fix 3V_S5 knee voltage		
A28	29		Add Wake# signal on EC pin57		
A29	17		Add Pi Filter near CN1 by EMI		
A30	4		Delete Q17,Q18,Q19		
A31	29		Change EC_ID0 signal from EC pin100 to EC pin35		
A32	11		Change R273 to Bead and mount C352		
A33	18		Add R423,R424,R425		
A34	18		Add L-C filter circuit near CN11		
A35	30		HOLE17 connect AGND		
A36	29		Change EC_ID0 signal from EC pin35 to EC pin106 Change EC_ID1 signal from EC pin106 to EC pin35		
A37	27		Reserve for trying LED light on PWR BD with ME		
A38	22		NC R371		
A39	29		Unmount R98		
A40	37		A short pad for EMI		
A41	29		EC Pin76 HDD_DETECT# connect to CN13 Pin12,Change R144 from 10K to 100K.		
A42	20		CN13 Pin12 connect to EC Pin76 HDD_DETECT# ,CN13 Pin18 through a 0 Ohm to GND.		
A43	10		Add D26 for CR2025 (non-chargeable RTC battery)		
A44	3-6		Modify CPU footprint for BGA ball of corner solder mask (open pad size to 14mail) at SIT-R		
A45	7-9		Modify NB footprint for BGA ball of corner solder mask (open pad size to 14mail) at SIT-R		
A46	30		Modify FP of HOLE6 to "H-C259D209P2" for ME.		
A47	16		Modify CAMVCC circuit from 3V to 5V for 5V camera module.		
A48	21		Modify values of ext. R,BOM and modify the power rail of MAX14550A & U5 & U31		
A49	29		Connect EC pin 83 to Flash WP# pin by "EC_WP#",modify BOM for ED_ID table.		
A50	25		Reserve 0 ohm for BT_DET#		
A51	27		Reserve 0603 0ohm for RF solution.		
A52	18		Reserve 0603 0ohm for RF solution.		
A53	10		Reserve charge circuit & Add diode for non-chargeable RTC battery		
A54	32		Change short PJP9 and PJP13 to add Bead (UPB201212T-800Y-N) for RF		
A55	30		Modify FP of HOLE15,HOLE14,HOLE13,HOLE12,HOLE11 for ME.		
A56	10		Change short FP of BT1 for customer request		
A57	29,21		Modify RTS5159 circuit for fix 144 Mhz NOISE		
A58	17,26		Add two 1206 fuse for CRT and Touch Pad		
A59	30		Add 2200p cap *13 for EMI		



Quanta Computer Inc.

PROJECT : Congo

Size	Document Number	Rev
	Engineer Change List	1A
Date: Thursday, October 22, 2009	Sheet 42 of 42	